

Rinnai



Rinnai INFINITY® A28i

Rinnai INFINITY® A28i Features

- ✓ Appliance output of 28 L per minute (at a 25°C rise)
- ✓ Ability to reduce input to 26 L/min and 199 MJ/h when closer flue clearances are required
- ✓ Suitable to use as a solar boost for solar thermal installations.
- ✓ Maximum outlet temperature of 85°C
- ✓ Adjustable wall brackets to allow easy alignment of existing water, gas and flue connections
- ✓ Simplified commission of internal appliances. Switch flue length settings without switch gas pressure setting
- ✓ Inbuilt controller for operating parameters and service & fault diagnostics

	INFINITY® A28i	
REU Number	REU-VCM2837FF-ZK	
Order code	INFA28FFL	INFA28FFN
Install location	Indoor	Indoor
Gas Type	LPG	NG
Thermal efficiency	83.5%	83.5%
Hot water capacity	1.4 - 37 L/min	
Hot water capacity (@ 25° C rise)	28 L/min	
Factory preset temperature	55°C	55°C
Max temperature	85°C	85°C
Gas Input	11 - 210 MJ/h	
Heat Output	48.8 kW	
Weight	21 kg	21 kg
Water - nominal operating pressure	220 - 1000 kPa	
Connection - hot	R3/4 (20mm)	
Connection - cold	R3/4 (20mm)	
Connection - gas	R3/4 (20mm)	
Ingress protection rating	IPX2	IPX2
Noise level (1m away)	54 dB(A)	54 dB(A)
Compliance - ES declaration number	DEC-000001840L3H1	
Power consumption		
Normal	66W	66W
Standby	2W	2W
Frost protection activation	104W	104W
Accessories		
Number of controllers	3	3

View the warranty conditions prior to purchase at rinnai.co.nz/warranty

Rinnai is constantly improving its products, and as such, information and specifications are subject to change without notice. For the most up-to-date information, go to rinnai.co.nz

This document has been printed using vegetable/soy-based inks on paper from environmentally responsible sources

Rinnai.co.nz | 0800 746 624

facebook.com/rinnainz